

# Hard Ballistic solutions (insert, helmet, shield)

Dyneema® grade	Areal density g/m <sup>2</sup>	Matrix	Performance
Dyneema® HB212	0.136 ± 0.005	Rubber	◆◆◆◆◆
Dyneema® HB210	0.136 ± 0.005	PUR	◆◆◆◆◆
Dyneema® HB80	0.145 ± 0.004	PUR	◆◆◆◆◆
Dyneema® HB56	0.233 ± 0.007	PUR	◆◆◆
Dyneema® HB50	0.235 ± 0.005	Rubber	◆◆◆
Dyneema® HB26	0.264 ± 0.007	PUR	◆◆
Dyneema® HB2	0.261 ± 0.005	Rubber	◆◆

■ Dyneema® Force Multiplier Technology platform

[www.dyneema.com](http://www.dyneema.com)

Dyneema® and Dyneema®, the world's strongest fiber™ are trademarks of DSM. Use of these trademarks is prohibited unless strictly authorized.

**Disclaimer**

All information, data, recommendations, etc. relating DSM Dyneema products (the Information) is supported by research. DSM Dyneema assumes no liability arising from (i) the application, processing or use made of the Information or products; (ii) infringement of the intellectual or industrial property rights of third parties by reason of the application, processing or use of the Information or products by the Buyer. Buyer shall (i) assume such liability; and (ii) verify the information and the products.